double speed-wax enhanced carnauba paste wax

Product Function

double speed-wax is an easy to use last stage paste wax for the protection of highly finished automobile paint systems. The carnauba wax used provides a deep rich glossy, highly water repellent and detergent resistant film. double speed-wax provides an economic and superior alternative to costly paste waxes which simply do not compete performance wise with this material.

Thoroughly wash vehicle with hot soapy water, only use salt-free automotive shampoos. Do not use wash and wax products.

Dry vehicle using chamois leather, or synthetic equivalent.

double speed-wax is not an abrasive polish, if your paintwork is faded, feels rough or has not been polished for a long period it will be necessary to use an abrasive polish and/or paint clay before application. Once prepared in this way regular application of double speed-wax will maintain a high gloss finish without the need for further use of abrasive polishes.

Work on shaded cool panels. Dampen the sponge applicator provided and wring out as much as possible before use. Apply wax extremely sparingly with with app pad in light circular motions and allow to dull for approx 5-10 minutes. Buff to a high shine using the blue microfibre cloth provided turn frequently.

Occasionally under certain humid application conditions the applied film may bloom after initial application and buffing. The bloom will disappear once the film is fully cured, or it can be removed immediately with a wipe down/buff with a slightly damp buffing cloth. This is a characteristic of the T1 carnauba wax used in the manufacture of this product.

Both applicator pad and microfibre cloth can be washed for re-use. Do not use fabric conditioner.





